



ALLIANCE
**EARTHMOVER &
MINING**

TRA: **G-2/L-2**
Speed Rating: **B**

Alliance 308 is a tire designed for rugged service on front-end loaders. Husky tread bars are sized and angled for maximum traction and specially contoured to resist tearing and chipping.

LOADER DOZER - 20.5-25 L-2



Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load			
								Speed			
		SW mm	OD mm					Static kmph	5 kmph	10 kmph	25 kmph
20.5-25 L-2	17	520	1492	658	4340	12PR	1.75	8700	6150	5440	4620
							2	9410	6640	5880	5000
							174A2	2.25	10080	7120	6300
						16PR	2.5	10720	7570	6700	5700
							2.75	11460	8090	7160	6090
							3	12060	8520	7540	6410
						181A2	3.25	12640	8930	7900	6720
							3.5	13200	9320	8250	7010
							3.75	13660	9650	8540	7260
						20PR	4	14190	10020	8870	7540
							4.25	14700	10380	9190	7810
							4.5	15200	10740	9500	8080

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load			
								Speed			
		SW mm	OD mm					Static kmph	5 kmph	10 kmph	25 kmph
20.5-25 L-2	17	520	1492	658	4340	12PR	2.1	9790	7890	7340	6800
							2.4	10580	8530	7940	7350
							174A2	2.7	11340	9140	8510
						16PR	3	12060	9720	9050	8380
							3.3	12890	10380	9670	8950
							3.6	13570	10930	10180	9430
						181A2	3.9	14220	11460	10670	9880
							4.2	14850	11960	11140	10310
							4.5	15370	12380	11530	10680
						20PR	4.8	15970	12860	11970	11090
							5.1	16540	13330	12410	11490
							5.4	17100	13780	12830	11880

Note: For above mentioned size 12 PR is no longer active for production.

Grader application