



ALLIANCE
AGRICULTURE

TRA: **R-1**
Speed Rating: **D**

The Alliance 350 is a special line of radial narrow tires for all types of cultivation, harvesting and spraying jobs. The tire is characterized by round shoulders for soil and crop protection. A tough casing and rigid belt provides all the advantages of radial construction. This tire is used as front wheel in Row Crop applications.

TRACTOR - 230/95R32(9.5R32)

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load							
								Speed							
								Non cyclic operation							
		Static kmph	10 kmph					15 kmph	25 kmph	40 kmph	50 kmph	65 kmph	70 kmph		
230/95R32(9.5R32)	W7 X 32	228	1251	582	3821	128D 131A8	0.8	1680	1100	980	870	800	770	730	660
							1.6	2650	1730	1540	1360	1260	1210	1150	1050
							2.8	3340	2180	1940	1720	1590	1520	1450	1320
							4	4140	2700	2410	2130	1970	1890	1800	1640
Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load							
								Speed							
								Cyclic Operation							
		10 kmph	15 kmph												
230/95R32(9.5R32)	W7 X 32	228	1251	582	3821	128D 131A8	1	1240	1130						
							2	1960	1780						
							3.5	2470	2250						
							5	3060	2790						

