



ALLIANCE  
CONSTRUCTION &  
INDUSTRIAL

TRA: E-2/L-2/G-2  
Speed Rating: A8

Alliance 326 Wide Grip Loader Dozer tire is a wide base tubeless tire. It is designed for superior self-cleaning, high traction and high flotation in all off road applications. Its heavy-duty nylon construction and weather ozone-resistant rubber compounds ensure longer tire life on all types of services.

TRANSPORT - 16/70-24 EM (405/70-24)

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load								
		SW inch	OD inch					Speed								
								9 mph	12 mph	16 mph	19 mph	25 mph	31 mph	34 mph	37 mph	40 mph
16/70-24 EM (405/70-24)	13.00SDC 12DC	16.0	46.4	22.7	144.1	10PR	25	5470	5360	5270	5160	5030	4870	4720	4480	4030
						143B 137D	29	5910	5800	5690	5580	5420	5270	5120	4850	4370
							33	6330	6220	6090	5980	5820	5640	5470	5200	4670
							36	6720	6610	6480	6370	6200	6010	5820	5530	5070
						14PR	40	7610	7470	7340	7190	6990	6790	6590	6240	5640
						152B 145D	44	8000	7850	7720	7560	7360	7140	6920	6570	5930
							47	8400	8250	8090	7940	7720	7500	7280	6900	6220
							51	8770	8620	8440	8290	8070	7830	7580	7210	6390

The Size 16/70-24 EM (405/70-24)-10PR is no longer active for production

