



ALLIANCE
AGRICULTURE

TRA: I-2
Speed Rating: A8

FarmPRO 327 Implement has a soil-friendly tread design characterized by central ribs and shoulder lugs. The central ribs together with a wide and flat contact area provide the lowest possible soil compaction and damage.

FARMPRO 327 IMPLEMENT - 500/50-17

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load							
								Speed							
		Drive Wheel						Free rolling							
		6 mph	16 mph					25 mph	31 mph	6 mph	16 mph	25 mph	31 mph		
500/50-17	16	19.7	37.8	17.1	111.8	10PR	22	4960	4230	3550	3200	7100	6040	5070	4560
						143A8⊕ 139B⊕ 130A8⊖ 126B⊖	26	5530	4700	3950	3550	7890	6720	5640	5070
							29	5860	4980	4190	3770	8420	7140	6010	5400
							36	8380	7120	6000	5400	10100	8580	7210	6480
						14PR	32	6090	5160	4340	3900	8800	7470	6280	5670
						149A8⊕ 145B⊕ 136A8⊖ 132B⊖	36	6550	5560	4670	4210	9480	8050	6770	6090
							40	6920	5890	4940	4450	10030	8530	7170	6460
							49	9900	8420	7060	6370	12040	10230	8600	7760
						18PR	44	7250	6170	5180	4660	10580	9000	7560	6810
						154A8⊕ 150B⊕ 141A8⊖ 137B⊖	51	7960	6750	5680	5110	11570	9830	8270	7440

The Size 500/50-17-10PR is no longer active for production

