



**ALLIANCE  
 AGRICULTURE**

TRA: I-3  
 Speed Rating: A8



FLOTATION

Alliance 328 VALUE PLUS is specially designed for low end applications like balers, wagons and other agricultural implements. It displays excellent flotation and self cleaning characteristics. The tire has moderate traction flotation profile and provides maximum soil protection and low compaction.

**IMPLEMENT - 500/60-22.5**

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load										
		SW inch	OD inch					Speed										
								Drive Wheel				Free rolling						
								6 mph	16 mph	25 mph	31 mph	6 mph	16 mph	25 mph	31 mph			
500/60-22.5	16.00DC	19.7	46.1	20.1	136.2	16PR	41	9860	8380	7030	6330	13910	11840	9940	8950			
						163A8↻	44	10250	8710	7320	6590	14480	12300	10340	9300			
						159B↻	46	10650	9060	7610	6860	15060	12790	10750	9680			
						151A8○	64	15230	12960	10870	9810	18080	15340	12900	11620			
						148B○												

1) When tires equip vehicles subject to haulage cyclic high load variation excluding transport application on long distances, i.e. vehicles used on roundtrips (e.g. from field to farm) where on one way the vehicle is empty & on the other way the gross vehicle mass exceeds two times the mass of empty vehicle (last two rows in the table). 2) When fitted on tractor steering wheels load capacities are 80% of free rolling and inflation pressure 20% higher. 3) For 10 KM/H and stationary use inflation pressure raised 20% and 25% respectively.

