

ALLIANCE  
AGRICULTURETRA: I-3  
Speed Rating: A8

Alliance 328 VALUE PLUS is specially designed for low end applications like balers,wagons and other agricultural implements. It displays excellent flotation and self cleaning characteristics. The tire has moderate traction flotation profile and provides maximum soil protection and low compaction.

**IMPLEMENT - 500/60-22.5**

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load											
								Speed											
		Drive Wheel				Free rolling				6 mph	16 mph	25 mph	31 mph	6 mph	16 mph	25 mph	31 mph		
		SW inch	OD inch			6		16	25	31	6	16	25	31	mph	mph			
500/60-22.5	16.00DC	19.7	46.1	20.1	136.2	16PR 163A8◎ 159B◎ 151A8◎ 148B◎	41 44 46 64	9860	8380	7030	6330	13910	11840	9940	8950				
								10250	8710	7320	6590	14480	12300	10340	9300				
								10650	9060	7610	6860	15060	12790	10750	9680				
								15230	12960	10870	9810	18080	15340	12900	11620				

1)When tires equip vehicles subject to haulage cyclic high load variationexcluding transport application on long distances, i.e. vehicles used on roundtrips (e.g. from field to farm) where on one way the vehicle is empty & onthe other way the gross vehicle mass exceeds two times the mass of emptyvehicle (last two rows in the table). 2) When fitted on tractor steering wheels load capacities are 80% of freerolling and inflation pressure 20% higher. 3) For 10 KM/H and stationary use inflation pressure raised 20% and 25%respectively.

