



ALLIANCE  
CONSTRUCTION &  
INDUSTRIAL

TRA: **R-3**  
Speed Rating: **A8**

The Alliance 329 is a diamond tread design tire built with a strong nylon construction. Its wide and extended tread protects shoulders and sidewalls against cutting and side snagging. The special cut and chip resistant compound ,heat resistant compound and the tires strong nylon construction provide long life to the tire.

TRACTOR - 18.4-26

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load								
								Speed								
								Field operation			Not high and sustained torque; Road transport					
								High Tor	Low Torque							
		SW inch	OD inch					6 mph	6 mph	12 mph	Static mph	6 mph	16 mph	19 mph	25 mph	31 mph
18.4-26	<b>W16L</b> <b>DW16</b> <b>W15L</b>	18.9	56.1	25.4	165.9	6PR	13	4190	5490	4720	9020	5890	4370	4190	3920	3570
						132A8	15	4450	5840	5000	9590	6260	4630	4450	4170	3790
							<b>16</b>	4720	6170	5290	10140	6610	4890	4720	<b>4410</b>	4010
						8PR	17	4960	6480	5560	10650	6950	5140	4960	4630	4210
						137A8	19	5180	6790	5820	11160	7280	5380	5180	4850	4410
							<b>20</b>	5420	7100	6090	11660	7610	5620	5420	<b>5070</b>	4610
						10PR	22	5620	7340	6310	12060	7870	5820	5620	5250	4780
						142A8	23	5820	7630	6530	12520	8180	6040	5820	5450	4960
							<b>26</b>	6260	8180	7010	13450	8770	6480	6260	<b>5840</b>	5310
						12PR	29	6500	8510	7300	14000	9130	6750	6500	6090	5530
						146A8	32	6880	9020	7720	14820	9660	7140	6880	6440	5860
							<b>33</b>	7080	9260	7940	15210	9920	7340	7080	<b>6610</b>	6020

Note: For above mentioned size 6 PR and 8 PR are no longer active for production. Recommended rim in red (Bold)

