



ALLIANCE
CONSTRUCTION &
INDUSTRIAL

TRA: R-3
Speed Rating: A8

The Alliance 330 Drive Wheel is a multi-purpose tire designed to provide high load capacity, significant traction and smooth ride comfort. It is suitable for on-the-road, design, and ozone resistant compounds provide long tread life. industrial and road construction equipment. The strong nylon construction, rugged design, and ozone resistant compounds provide long tread life.

TRACTOR HEAVY DUTY - 28L-26

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load								
								Speed								
		SW inch	OD inch					Drive Wheel				Free rolling				
								6 mph	16 mph	25 mph	31 mph	Static mph	6 mph	16 mph	25 mph	31 mph
28L-26	DW25A	28.1	62.6	27.6	183.5	12PR	19	13320	11290	10650	9700	26920	14640	12410	11710	10650
						167A8	22	14460	12280	11570	10540	29260	15900	13490	12720	11570
							23	15010	12740	12020	10940	30400	16510	14000	13220	12040
						16PR	15	11310	9590	9040	8220	22860	12430	10540	9940	9040
							28	16450	13960	13160	11970	33270	18080	15320	14460	13160
						173A8	30	17440	14790	13960	12700	35300	19180	16270	15340	13960
							32	17920	15190	14330	13050	36270	19710	16710	15760	14350

* Available in OD = 61 (1550 mm) defined as B-61. The Size 28L-26-12PR is no longer active for production

