

**ALLIANCE
FORESTRY**

TRA: **LS-2**
Speed Rating: **A6**

Alliance Forestar 345 LS-2 is designed for skidders and feller bunchers. The sturdy construction makes it well-equipped to withstand the toughest environment. High traction and excellent self-cleaning make it an ideal choice for the most challenging terrains.

LS-2 FORESTRY - 28L-26



Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load				
								Speed				
								Constant load application				
								logging or forestry service				
		SW inch	OD inch					Static mph	9 mph	16 mph	19 mph	25 mph
28L-26	DW25A	28.1	64.5	29.4	191.4	12PR	17	20420	9080	8310	7560	6810
						154A6 166A2	19	21360	9500	8710	7920	7120
							20	22330	9920	9110	8270	7450
						16PR	22	23520	10450	9590	8710	7850
						160A6 172A2	23	24470	10870	9970	9060	8160
							28	27030	12020	11000	10010	9020
						20PR	29	27560	12260	11220	10210	9190
						165A6 177A2	32	29100	12940	11860	10780	9700
							35	30670	13630	12500	11350	10230
						26PR	41	33580	14930	13670	12430	11200
						173A6 184A2	46	36240	16120	14770	13430	12080
							52	38690	17200	15760	14330	12900
						12PR	22	10580				
							24	11090				
							25	11570				
							27	12190				
							28	12680				
						160A6 172A2	33	14020				
							35	14290				
						165A6 177A2	38	15100				
							41	15900				
						26PR	35	17420				
						173A6 184A2	38	18810				
							57	20060				

Note: For above mentioned size 12 PR is no longer active for production.