



GALAXY
AGRICULTURE

TRA: **R-1**
Speed Rating: **A8**



SPECIAL
COMPOU
ND



TUBE TYPE

Alliance 347 is a drive wheel tractor tire with higher number of 23 degree lugs. It provides maximum traction on all types of soil and provides a smooth drive. A strong nylon carcass guards against mechanical failures and moisture deterioration. The tire is engineered with breakers for better protection against punctures.

TRACTOR - 23.1-26



Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load					
		SW inch	OD inch					Speed					
								Tractor application					
								Static mph	6 mph	12 mph	19 mph	25 mph	31 mph
23.1-26	DW20	23.1	63.2	27.7	183.0	153A8	12	11870	7740	6350	5520	5160	4690
							17	15060	9820	8050	7010	6550	5960
							23	17850	11640	9550	8300	7760	7060
							25	18510	12070	9900	8610	8050	7320
23.1-26 Steel Belted	DW20	23.1	63.2	27.7	183.0	159A8	12	11970	7800	6400	5570	5200	4740
							17	15160	9890	8110	7050	6590	6000
							23	17950	11710	9600	8350	7800	7100
							29	20440	13330	10930	9510	8890	8080
							33	22190	14470	11860	10320	9650	8780
23.1-26 Steel Belted	DW20	23.1	63.2	27.7	183.0	159A8	12	11970	7800	6400	5570	5200	4740
							17	15160	9890	8110	7050	6590	6000
							23	17950	11710	9600	8350	7800	7100
							29	20440	13330	10930	9510	8890	8080
							33	22190	14470	11860	10320	9650	8780
23.1-26	DW20B X 26	23.6	63.2	28.9	188.8	159A8	12	11970	7800	6400	5570	5200	4740
							17	15160	9890	8110	7050	6590	6000
							23	17950	11710	9600	8350	7800	7100
							29	20440	13330	10930	9510	8890	8080
							33	22190	14470	11860	10320	9650	8780
23.1-26	DW20B X 26	23.6	63.2	28.1	190.9	153A8	12	11870	7740	6350	5520	5160	4690
							17	15060	9820	8050	7010	6550	5960
							23	17850	11640	9550	8300	7760	7060
							25	18510	12070	9900	8610	8050	7320
							23.1-26	DW20B X 26	23.1	63.2	28.3	189.1	153A8
17	15060	9820	8050	7010	6550	5960							
23	17850	11640	9550	8300	7760	7060							
25	18510	12070	9900	8610	8050	7320							

Steel Belt available in 14 PR only. Note: For above mentioned size 8 PR and 10 PR are no longer active for production. 1) For stationary service (0 km/h) and speed up to 10 km/h inflation pressure must increase by 20%. 2) Field dual: 88% of field load, Field triple :82% of field load. *Alliance allows for Free Rolling application: Load capacity to be increased by 20%, after increasing the inflation pressure by 20%.