



**ALLIANCE  
 AGRICULTURE**

TRA: **R-1W**  
 Speed Rating: **D**

Agri-star 385 Radial tire is a part of the 85 Series and represents our focus on developing tires that meet the demands of extensive developments in the tractor industry. The tread-pattern is designed with specific lug construction and strength required for modern high HP/ speed tractors. Special focus is given to the flexibility characteristics of the tire. The 385 promises a smooth and comfortable ride. Strong textile casing combined with high quality tread and sidewall rubber compounding ensures better tire life.

**TRACTOR RADIAL HIGH SPEED - 460/85R34**

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load									
		Speed															
		Field operation						Not high and sustained torque; Road transport									
		High Tor	Low Torque														
		6 mph	6 mph					12 mph	Static mph	6 mph	16 mph	19 mph	25 mph	31 mph	40 mph		
460/85R34	W16L, W15L, W14L	19.1	65.1	29.5	192.6	144D 147A8	12	4830	6330	5420	9480	6200	4890	4740	4520	4320	4120
							15	5490	7190	6170	10800	7060	5560	5400	5140	4940	4700
							19	6420	8400	7190	12570	8200	6480	6280	6000	5730	5470
							23	7230	9480	8110	14200	9260	7320	7100	6770	6480	6170

The Size 460/85R34 ( LI - 147A8/144D(\*) ) is no longer active for production

