



ALLIANCE
AGRICULTURE

TRA: I-2
Speed Rating: F

Alliance 390 Heavy Duty steel belted flotation radial Implement tires belong to the Agri-Transport series combining the best of flotation characteristics with the best of radial construction to provide excellent performance both on and off road. The tires can be used for multiple machines in on/off-the-road applications. MPT tires can go upto 100 km/h and are best suited for tough applications compared to the standard range.

IMPLEMENT - 600/55R26.5

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load							
								Speed							
								Mixed application							
		SW inch	OD inch					Static mph	6 mph	16 mph	19 mph	25 mph	31 mph	37 mph	40 mph
600/55R26.5	AG 20.00	24.6	53.3	24.1	161.6	165D	12	10190	7980	7010	6700	6020	5360	4740	4430
							17	12880	10080	8840	8470	7610	6770	6000	5600
							23	15260	11950	10490	10030	9020	8030	7100	6640
							29	17390	13600	11950	11420	10270	9150	8090	7560
							35	19380	15170	13320	12720	11460	10190	9020	8640
							41	21190	16580	14550	13910	12520	11160	9860	9220
							46	22930	17950	15740	15060	13560	12060	10670	9970
							52	24540	19200	16870	16120	14510	12920	11420	10670
							58	26130	20440	17950	17150	15430	13740	12150	11350

1) When fitted on tractor steering wheels load capacity is 80% of free rolling and inflation pressure 20% higher. 2) For 10 km/h and stationary use inflation pressure raised 20% and 25% respectively. 3) All sizes are suited for Air pressure control system. Note-The above pattern is designed for OFF road application.

