



ALLIANCE  
AGRICULTURE

TRA: I-2  
Speed Rating: F

Alliance 390 Heavy Duty steel belted flotation radial Implement tires belong to the Agri-Transport series combining the best of flotation characteristics with the best of radial construction to provide excellent performance both on and off road. The tires can be used for multiple machines in on/off-the-road applications. MPT tires can go upto 100 km/h and are best suited for tough applications compared to the standard range.

IMPLEMENT - 30.5LR32

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load					
								Speed					
								Mixed application					
		SW inch	OD inch					Static mph	6 mph	16 mph	19 mph	25 mph	31 mph
30.5LR32	DW27A	31.1	70.9	31.7	213.8	181 B	12	19310	13360	11510	10910	9660	8400
							22	27890	19290	16620	15760	13960	12130
							29	33000	22820	19670	18650	16510	14350
							36	37630	26020	22420	21280	18810	16360
							44	41840	28930	24910	23660	20920	18190

1) When fitted on tractor steering wheels load capacity is 80% of free rolling and inflation pressure 20% higher. 2) For 10 km/h and stationary use inflation pressure raised 20% and 25% respectively. 3) All sizes are suited for Air pressure control system. Note-The above pattern is designed for OFF road application.

