



ALLIANCE
AGRICULTURE

TRA: **R-1W**
Speed Rating: **A8**

FarmPRO 85 series of agricultural radial tires have multi angle lug design with steep angles at the center that enables smooth ride along with self cleaning characteristics. The shallow angle at shoulder provides superior traction. These tires are characterized by reinforced construction in the bead area and have enhanced bead to bead distance to facilitate perfect fit on the rim. The regular cavity in the tread design ensures a straighter sidewall.

TRACTOR - 340/85R28

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load							
								Speed							
		Tractor Application													
		Static mph	6 mph					16 mph	19 mph	25 mph	31 mph				
340/85R28(13.6R28)	W12 X 28	14.0	50.7	23.3	147.8	127A8 127B	12	5690	3700	2730	2650	2470	2470		
							17	7360	4810	3550	3420	3200	3200		
							20	8110	5290	3920	3770	3530	3530		
							23	8890	5800	4280	4120	3860	3860		
Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load							
								Speed							
		Drive Wheel Application													
			6 mph					9 mph	16 mph	19 mph	25 mph	31 mph	40 mph	Static mph	
340/85R28(13.6R28)	W12 X 28	14.0	50.7	23.3	147.8	127D	12	3700	3310	2930	2840	2710	2600	2470	5690
							17	4810	4280	3790	3680	3510	3350	3200	7340
							20	5290	4720	4190	4060	3860	3700	3530	8110
							23	5800	5180	4560	4430	4230	4060	3860	8860

*Alliance allows for free rolling application:Load capacity to be increased by 20%,after increasing the inflation pressure by 20%

