https://yokohama-atg.com Generated on: 17 Apr, 2024



ALLIANCE **AGRICULTURE**

TRA: **R-1W** Speed Rating: **A8** The Alliance FarmPRO 70 Series Radial is a highly versatile range that represents the family of modern agricultural radial tires. The multi-angle lug design with steep angles at the center enables a smooth ride, along with self-clearing characteristics. In addition, the shallow angle at the shoulder provides superior traction. These tires are characterized by reinforced construction in the bead area and have enhanced bead-to-bead distance to facilitate a perfect fit on the rim. The regular cavity in the tread design ensures a straighter sidewall, which enhances the tire's visual appeal

TRACTOR - 420/70R30

Size		Unloaded Dimension					Load Index		Inflation Pressure psi	Recommended Load						
					ided atic	Rolling				Speed						
	Rim			rad		Circumference inch	PR Symbols			Non cyclic operation						
		SW inch	OD inch							Static mph	6 mph	9 mph	16 mph	19 mph	25 mph	31 mph
420/70R30	W13 X 30 W12 X 30	16.5					134A8 134B		12	6900	4500	4010	3330	3220	3000	3000
			55.0	24	1.6	162.4			17	8890	5800	5180	4280	4120	3860	3860
				_					20	9900	6460	5750	4760	4610	4300	4300
									23	10760	7010	6260	5180	5000	4670	4670
Size				Unlo	adad		atic Rollii Circumfe incl					Inflation Pressure psi		Recommended Load		
	Ι.,	Dies		Unloaded Dimension		Loaded Sta				Load Inc	lex			Speed		
	Rim					radius inch				PR Symbo	ls			Cyclic operation		
				SW nch	OD inch									6 mph		9 mph
												15		2310{hlc} 2		10{hlc}
420/70R30		30 W1	2 1	6.5	55.0	24.6		162	.4	134A8 134B		22		6570 59		5980
	>	30	30		55.0	2	102.			1040		26		7320	7320 66	
												29		7940	1	7250



^{*}Alliance allows for free rolling application:Load capacity to be increased by 20%, after increasing the inflation pressure by 20%