



ALLIANCE
CONSTRUCTION &
INDUSTRIAL

TRA: R-4
Speed Rating: A5

The all-new pattern for skid steer SK-906 is more open and deeper at the shoulders for good traction in soft soil. Solid center for long wear on hard surfaces. Open, deep shoulders for off-road traction. Has a highly abrasion-resistant tread compound. Features a rim shield protector and a heavy sidewall. The tread radius is relatively flat which is good for wear on hard surfaces.

SKIDSTEER - 10x16.5NHS

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load	
								Speed	
								Skid Steer	
		SW inch	OD inch					Static mph	6 mph
10-16.5NHS	8.25 X 16.5	10.2	28.9	14.0	90.2	12 138A2	90	8220	5200

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load	
								Speed	
								SkidSteer	
		SW inch	OD inch					Static mph	6 mph
10-16.5 NHS	8.25 X 16.5	10.4	30.4	14.0	90.2	10 134A2	75	7390	4670

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load	
								Speed	
								Skidsteer	
		SW inch	OD inch					6 mph	
10-16.5NHS	8.25X16.5	10.2	30.2	13.7	92.4	8 130A2	59	4190	

