




PRIMEX
FORESTRY

TRA: **LS-2**
 Speed Rating: **A6**



Primex LogMonster LS-2 is an advanced diagonal forestry tire developed for use by forestry heavy machines and logging industry. It is designed to work under extreme terrain conditions and provide long tire life. Design allows high traction with low slippage. It is constructed with strong nylon and steel belts, high under tread gauge, high and robust lugs, strong and thick sidewalls, special tread compound and protective mudguard.

LS-2 - 35.5L-32

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load				
		SW inch	OD inch					Speed				
								Log Skidder Application				
								Static mph	9 mph	16 mph	19 mph	25 mph
35.5L-32	DH31/DH31H	35.3	79.1	36.2	235.4	26PR	22	39530	17570	16090	14640	13180
						183A6	26	43980	19560	17920	16290	14660
							29	46780	20790	19070	17330	15600
							35	52100	23150	21230	19290	17360

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load					
		SW inch	OD inch					Speed					
								Constant load application					
								cable/grapple skidders	logging or forestry service				
									6 mph	Static mph	9 mph	16 mph	19 mph
35.5L-32	DH31	35.5	79.2	35.9	235.0	20PR 177A6/189A2	23	NA	40540	18010	16510	15010	13510
							25	NA	42020	18670	17130	15570	14000
							26	NA	43450	19310	17700	16090	14480
							28	21010	NA	NA	NA	NA	NA
							30	21780	NA	NA	NA	NA	NA
							31	22710	NA	NA	NA	NA	NA

