https://yokohama-atg.com Generated on: 19 Apr, 2024



GALAXY AGRICULTURE

TRA: **I-2** Speed Rating: **B** Galaxy Impmaster 350 I-2 is made with a wide tread & shoulder profile to enhance flotation characteristics so as to reduce soil compaction. It is made with a tread depth that is 33.3% deeper than Competition. Having a deeper tread results in much longer tread life and eliminates practically all field hazard damages.

IMPLEMENT - 11-22.5NHS

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load				
								Speed				
								Free rolling				
		SW inch	OD inch					Static mph	6 mph	16 mph	19 mph	25 mph
11- 22.5	8.25x22.5	10.9	41.1	18.9	125.3		12	3460	2710	2250	2090	1900
						14PR	29	5930	4630	3840	3590	3240
						148A6	58	8890	6950	5750	5380	4850
							90	11460	8950	7430	6950	6260
									Recom	mended	d Load	
		Unloa Dime		Loaded	Rolling	Load Index	Inflation			mended Speed	d Load	
Size	e Rim			Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi					
Size	e Rim			Static radius	Circumference	PR	Pressure	Static mph		Speed		25 mph
Size	e Rim	Dime	nsion OD	Static radius	Circumference	PR Symbols	Pressure		Fro	Speed ee rollin 16	g 19	
11-	9.25	SW inch	OD inch	Static radius inch	Circumference inch	PR	Pressure psi	mph	From 6 mph	Speed ee rollin 16 mph	g 19 mph	mph
	9.25	Dime	nsion OD	Static radius	Circumference	PR Symbols	Pressure psi 12	mph 3790	6 mph 2950	Speed ee rollin 16 mph 2450	9 19 mph 2290	mph 2070

