



**GALAXY
 AGRICULTURE**

TRA: **F-2**
 Speed Rating: **A6**



Optimised rib design to achieve easy driving ON/OFF road application. Tire life enhancement by a. Special compound designed for low wear b. Additional rubber at centre rib. Specially designed RIB angles and radius for better road ability .Improved sidewall deflection on loading for better stability. Aesthetically improved modern F2 design with complete size range in Galaxy. Additional rubber layer to provide under tread to improve penetration resistance

TRACTOR DIAGONAL - 7.50-16

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load						
		SW inch	OD inch					Speed						
								Mixed application						
								Static mph	6 mph	12 mph	16 mph	19 mph	25 mph	
7.50-16	5.50FX16	8.1	31.7	14.2	96.1	8PR	39	3700	5340	1980	1720	1610	1280	
							44	3950	2580	2120	1830	1720	1370	
							103A6/ 96A8	48	4170	2710	2230	1940	1810	1460
								54	4430	2890	2600	2230	1930	1540
							6PR	29	3090	2030	1650	1430	1350	1080
								32	3310	2160	1760	1540	1430	1150
						98A6/ 90A8		36	3550	2320	1900	1650	1540	1240
								41	3810	2490	2230	1900	1650	1320

