



ALLIANCE
EARTHMOVER &
MINING

TRA: NA
Speed Rating: D

The Alliance 212 D.S. Logger is an ideal design (in Earthmoving and Loaders) for heavy-duty jobs under all working conditions. Its special non-directional tread design and heavy-duty all nylon carcass results in a strong tire that withstand cuts, snags and bruises under all service conditions.

TRANSPORT - 13.00-25

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load								
		SW inch	OD inch					Speed								
								9 mph	12 mph	16 mph	19 mph	25 mph	31 mph	34 mph	37 mph	40 mph
13.00-25	10 8.5	25.6	50.6	22.9	149.6	16PR	36	6660	6550	6440	6310	6130	5950	5840	5530	5070
							40	7030	6920	6790	6660	6480	6280	6150	5840	5340
							44	7410	7280	7140	7010	6810	6610	6480	6150	5620
						152B 146D	47	7760	7610	7470	7340	7120	6920	6790	6440	5890
							51	8090	7960	7800	7670	7450	7230	7080	6720	6150
							54	8440	8290	8140	8000	7760	7540	7390	7010	6420
						58	8770	8620	8440	8290	8070	7830	7670	7280	6610	
						18PR	62	8970	8800	8640	8490	8250	8000	7850	7450	6810
						154B 149D	65	9260	9110	8930	8770	8510	8270	8110	7690	7170
							69	9590	9410	9240	9060	8820	8550	8380	7960	7280
						20PR	73	9880	9700	9520	9350	9080	8820	8640	8200	7610
						156B 151D										

Note : For above mentioned size only 16 PR is active for production.

