



PRIMEX  
AGRICULTURE  
  
TRA: I-3  
Speed Rating: A8

The Imp Trak Metric is designed for free-rolling wheels where flotation and limited soil compaction is desired. The Imp Trak Metric is available in a large range of metric sizes.

HIGH FLOTATION/TERRA - 550x60-22.5

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load							
								Speed							
		Drive wheel						Free rolling							
		6 mph	16 mph					25 mph	31 mph	6 mph	16 mph	25 mph	31 mph		
550x60-22.5	16	20.9	49.8	22.1	NaN	16PR	17	7960	6770	5690	5120	11240	9550	8030	7220
						166A8/162B 154A8/150B	26	10100	8580	7210	6490	14220	12100	10160	9150
						33	11570	9830	8270	7440	16340	13890	11670	10500	
Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load							
								Speed							
		Drive wheel						Free rolling							
		6 mph	16 mph					25 mph	31 mph	6 mph	16 mph	25 mph	31 mph		
550x60-22.5	16	20.9	49.8	22.1	NaN	16PR	35	10160	8640	7250	6530	14350	12190	10250	9240
						166A8⌚ 162B⌚ 154A8⌚ 150B⌚	38	10650	9060	7610	6860	15040	12790	10740	9660
							44	11570	9830	8270	7450	16360	13910	11680	10520
							59	16560	14070	11820	10650	19620	16690	14020	12610

