https://yokohama-atg.com Generated on: 26 Apr, 2024



ALLIANCE **AGRICULTURE**

TRA: **HF-2** Speed Rating: **D** Alliance Agriflex+ 389 VF introduces the next round of innovation: the world's first VF flotation tire offers the possibility to be operated at 30% lower inflation pressure as a conventional flotation tire. With Agriflex+ 389 we have trailer tires which allow to mirror the pressure of VF tires on today's high horsepower tractors. This significantly reduces the footprint pressure and thus results in low soil compaction.

Agri Transport - VF 600/55R26.5 IMP

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load							
								Speed							
								MIXED APPLICATION							
		SW inch	OD inch					Static mph	6 mph	12 mph	19 mph	25 mph	31 mph	37 mph	40 mph
VF600/55R26.5	AG20 X 26.5	24.8	53.1	23.1	160.0	167D 167D	12	10600	8530	7920	7340	6700	6090	5510	5200
							17	13490	10850	10050	9330	8530	7740	7010	6610
							23	16870	13560	12570	11660	10670	9680	8770	8270
							29	18560	14930	13820	12830	11730	10650	9630	9090
							35	21360	17170	15920	14770	13510	12260	11110	10470
							41	24520	19710	18250	16930	15500	14070	12740	12020

Highlighted values are to be used with Tire Inflating System

