



ALLIANCE  
AGRICULTURE  
  
TRA: **HF-2**  
Speed Rating: **D**

The Alliance 128 HS (High Speed Flotation I-128) is designed with good self-cleaning characteristics which is suitable for on and off-the-road agricultural service on trailers and implements.

High Flotation HF-2, HF-3, and HF-4 - 800/35-22.5

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load						
								Speed						
								Free rolling						
		SW inch	OD inch					6 mph	12 mph	19 mph	25 mph	31 mph	37 mph	40 mph
800/35-22.5	28.00DC 26.00DC 24.00DC	31.5	46.1	20.7	138.1	162D□ 169A8	23	13490	12150	10780	9630	8660	8180	7960
							26	14440	13010	11550	10320	9280	8770	8510
							29	15340	13800	12280	10960	9860	9300	9040
							32	16230	14620	12990	11600	10430	9860	9570
							35	17060	15370	13650	12190	10980	10360	10050
							38	17900	16120	14330	12790	11510	10870	10470
							52	21470	19340	17200	15340	13800	13050	12570

Highlighted row indicates- High load variation (HLV) Max. distance for drive wheel should not exceed 1 km.

