



AGRICULTURE

TRA: I-2
 Speed Rating: F



ALL STEEL FLOTATION

392 is an all steel tire with an F speed rating for high speed agri-transport operations. High load carrying capacity, protection against cuts & punctures, low soil compaction and low rolling resistance are some of its key features. It is suitable for heavy duty applications. Its unique tread design ensures high traction in all terrains. It is suitable for sandy and soft soil operations.

HEAVY DUTY FLOTATION - 24R20.5 MPT All Steel

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load									
		SW inch	OD inch					Speed									
								Mixed application									
								Static mph	6 mph	16 mph	19 mph	25 mph	31 mph	37 mph	40 mph	43 mph	50 mph
24R20.5 MPT All Steel	18	23.6	54.0	24.6	166.2	176F	15	13670	9830	7390	6830	6280	6130	6020	5890	5730	5470
							22	17370	12500	9370	8690	7980	7780	7650	7470	7300	6950
							29	20570	14790	11110	10270	9460	9220	9040	8840	8640	8220
							36	23440	16870	12660	11710	10780	10490	10320	10080	9830	9370
							44	26080	18760	14090	13030	11990	11680	11460	11200	10960	10430
							51	28550	20550	15410	14290	13140	12790	12570	12280	11990	11420
							58	30870	22220	16670	15430	14200	13820	13580	13270	12960	12350
							65	33070	23810	17860	16540	15210	14820	14550	14220	13890	13230
							73	35160	25310	18980	17590	16180	15760	15480	15120	14770	14070
							80	37210	26790	20080	18610	17110	16670	16380	16010	15630	14880
87	39130	28180	21140	19580	18010	17530	17220	16820	16450	15650							

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%). Steel belt available in 176F only.

