



ALLIANCE
AGRICULTURE

TRA: I-2
Speed Rating: D

Alliance 381 Agriflex is an IF steel belted radial flotation tire that has been developed to serve the needs of specific niche applications on sensitive surfaces, which require optimized soil and plant protection. The unique rib type pattern, enables a large footprint and low ground pressure. The shoulder lugs prevent any excessive tire slip and any consequent damage to the surface. Its specially designed bead area ensures better load carrying capacity.

IMPLEMENT - IF 240/80R15 Steel Belted

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load							
								Speed							
								Mixed application							
		SW inch	OD inch					Static mph	6 mph	16 mph	19 mph	25 mph	31 mph	37 mph	40 mph
IF 240/80R15 Steel Belted	8LBX15	9.6	30.1	13.6	91.3	125D	15	3950	3090	2710	2600	2340	2070	1830	1720
							22	5030	3920	3440	3290	2980	2650	2340	2180
							29	5930	4650	4080	3900	3510	3130	2760	2580
							36	6750	5270	4630	4430	3990	3550	3130	2930
							44	7500	5860	5160	4920	4430	3950	3480	3260
							46	7800	6110	5360	5140	4610	4100	3640	3400
							52	8380	6550	5750	5490	4940	4410	3900	3640

* Alliance allows for free rolling application: Load capacity to be increased by 20%, after increasing the inflation pressure by 20%. Steel belt available in (FR 125D / DW 113D) only. Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

