

ALLIANCE
CONSTRUCTION & INDUSTRIAL

TRA: **E-2**
Speed Rating: **B**

The tread pattern of 225 MPT is designed for self-cleaning as well as for smooth on road driving. The diagonal lug design of the tire provides best traction in all services, terrain and weather conditions besides improving resistance to side slips. Its wide based design provides high flotation properties and permits low inflation pressure. For free rolling and better mileage on road service, it is recommended to mount tires in opposite direction than usual.

EXCAVATOR - 10.00-20ML

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load
		SW inch	OD inch					Speed
								31 mph
10.00-20ML	7.5 X 20	10.8	41.9	19.7	128.6	16 148B	115	6950

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load						
								Speed						
								speed						
		SW inch	OD inch					Static mph	6 mph	12 mph	16 mph	19 mph	25 mph	28 mph	31 mph
10.00-20ML	7.5 X 20	10.8	41.9	19.9	127.6	14 145B 143B	80	11550	6750	6500	6390	6330	6110	5860	5750
							87	12130	7080	6830	6700	6640	6390	6150	6040
							96	12850	7500	7250	7120	7060	6790	6530	6390

Note : For above mentioned size 12 PR is no longer active for production.