



**ALLIANCE
 AGRICULTURE**

TRA: **IMP**
 Speed Rating: **A6**



Alliance Trailer 448 is specially designed for trailer applications. The non-directional tread pattern with high lug to void ratio provides outstanding maneuverability and stability. Presence of abrasion resistant compound ensures excellent durability. High traction with low rolling resistance assures improved productivity making it a perfect choice for customers worldwide.

IMPLEMENT - 9.00-16

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load							
		SW inch	OD inch					Speed							
								Free rolling							
		Static mph	6 mph	16 mph	19 mph	25 mph									
9.00-16	6.50H x 16 6.00Gx16	10.2	36.5	17.0	109.7	16PR	29	3970	3110	2580	2400	2160			
							58	5930	4630	3840	3590	3240			
						137A6	87	7540	5890	4870	4560	4100			
							104	8380	6550	5420	5070	4560			
						18PR	29	3920	3060	2560	2380	2140			
							58	5930	4630	3840	3590	3240			
						138A6	87	7500	5860	4850	4540	4080			
							110	8580	6700	5580	5200	4670			

* Alliance allows for free rolling application: Load capacity to be increased by 20%, after increasing the inflation pressure by 20%. Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

