



ALLIANCE
AGRICULTURE

TRA: **R-1**
Speed Rating: **A8**

The 23 degree tread offers maximum traction while distinct terracing in the space between the lugs is designed to enhance self-cleaning and provide constant traction in soft soil and mud. The neutral casing mould design minimizes stresses from the under inflated to the inflated tire, resulting in enhanced long-term reliability.

TRACTOR - 16.9-38

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load					
								Speed					
								Tractor application					
		SW inch	OD inch					Static mph	6 mph	12 mph	19 mph	25 mph	31 mph
16.9-38	W15L X 38 W15A X 38 W14L X 38 DW14A X 38	16.9	66.5	30.7	197.2	12 142A8	12	7450	4860	3990	3470	3240	2950
							17	9430	6150	5040	4390	4100	3730
							23	11160	7280	5970	5190	4850	4410
							29	12730	8300	6810	5920	5530	5040
							32	13440	8760	7190	6250	5840	5320

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

