



ALLIANCE  
AGRICULTURE  
  
TRA: I-2  
Speed Rating: D

The Agriflex+ 381 is a tire with a flat tread profile and large footprint. It puts more rubber on the ground. This unique rib-type pattern leads to effective steering and improved lateral traction, thereby reducing soil compaction and prolonging tire life. Moreover, the shoulder lugs prevent any excessive tire slips and consequently save the tire surface from further damage.

IMPLEMENT - VF 445/50R22.5

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load							
								Speed							
								Mixed application							
		SW inch	OD inch					Static mph	6 mph	16 mph	19 mph	25 mph	31 mph	37 mph	40 mph
VF 445/50R22.5	AG14.00 X 22.5	17.2	40.0	17.9	123.0	167D	15	9130	7140	6260	6000	5400	4810	4260	3970
							22	11550	9040	7940	7580	6830	6090	5380	5030
							29	13690	10710	9410	9000	8090	7210	6370	5950
							51	18960	14840	13030	12460	11220	9990	8820	8250
							58	20480	16030	14070	13450	12100	10780	9520	8910
							65	21960	17170	15080	14420	12990	11550	10210	9550
							73	23330	18250	16030	15320	13800	12280	10850	10140
							80	24650	19290	16930	16180	14570	12960	11460	10710
							87	25900	20280	17790	17020	15320	13630	12060	11270
							97	27650	21630	18980	18140	16340	14530	12850	12020

