



**GALAXY
EARTHMOVER &
MINING**

TRA: **E-3/L-3**
Speed Rating: **A2**

LDSR 300 is specially constructed for wheel loaders operating in the toughest environments. Transportation of heavy load demands excellent stability and robustness. Sturdy radial construction coupled with strong sidewall protector provides LDSR 300 superior strength and endurance to withstand challenging terrains. Premium tread compounds provide excellent protection against lug-tearing and chunking, helping the machine to perform efficiently without any downtime shaped tread pattern with stepped lugs ensure optimal traction and enhanced self cleaning assuring high productivity.

EARTHMOVER - 26.5R25

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load										
		SW inch	OD inch					Speed										
								Load capacity for Loader Application										
								Static mph	Creep mph	3 mph	6 mph	9 mph	12 mph	16 mph	19 mph	25 mph		
26.5R25	22.00/3.0	26.7	68.3	29.7	207.1	209A2	94	65260	53020	46520	40790	35490	34280	32630	31420	28550		

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load										
		SW inch	OD inch					Speed										
								Load capacity for Earthmover application kg (lbs)										
								9 mph	12 mph	16 mph	19 mph	22 mph	25 mph	28 mph	31 mph	34 mph	37 mph	40 mph
26.5R25	22.00/3.0	26.7	68.3	29.7	207.1	193B	76	28440	28000	27340	26900	26460	26020	25790	25350	24910	23810	22270

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

