



ALLIANCE
**EARTHMOVER &
MINING**

TRA: **G-2/L-2**
Speed Rating: **B**

Alliance 308 is a tire designed for rugged service on front-end loaders. Husky tread bars are sized and angled for maximum traction and specially contoured to resist tearing and chipping. The overlapping lugs ensure smooth rolling on any type of surface and the spacing between lugs provides self-cleaning properties. It is built with ozone and weather-resistant compounds and has a strong nylon construction.

LOADER DOZER - 17.5-25 L-2



Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load			
								Speed			
		Hard Improved Surfaces									
		Static mph	3 mph					6 mph	16 mph		
17.5-25 L-2	14 14SDC	17.5	53.1	23.6	155.1	12PR	48	21190	17060	15900	14730
							52	22310	17970	16730	15500
							171A2	57	23370	18830	17530
						61		24410	19670	18300	16950
						16PR	65	25240	20330	18940	17530
							70	26190	21100	19640	18190
							177A2	74	27140	21870	20350
						83		28970	23350	21740	20130
						20PR	87	30160	24300	22620	20940
							91	31040	25000	23280	21560
							181A2	96	31900	25710	23920
						100		32740	26370	24560	22730

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load			
								Speed			
		Off-the road									
		Static mph	3 mph					6 mph	16 mph		
17.5-25 L-2	14 14SDC	17.5	53.1	23.6	155.1	12PR	40	18830	13290	11770	10010
							44	19820	14000	12390	10540
							171A2	47	20770	14680	12990
						51		21690	15320	13560	11530
						16PR	54	22440	15850	14020	11930
							58	23280	16450	14550	12370
							177A2	62	24120	17040	15080
						69		25750	18190	16090	13690
						20PR	73	26810	18940	16760	14240
							76	27580	19490	17240	14660
							181A2	80	28350	20040	17730
						83		29100	20550	18190	15450

Note: For above mentioned size 20 PR is no longer active for production.

Grader application