



**ALLIANCE
EARTHMOVER &
MINING**

TRA: **G-2/L-2**
Speed Rating: **B**

Alliance 308 is a tire designed for rugged service on front-end loaders. Husky tread bars are sized and angled for maximum traction and specially contoured to resist tearing and chipping.

LOADER DOZER - 20.5-25 L-2



Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load			
								Speed			
		Off-the road									
		Static mph	3 mph					6 mph	16 mph		
20.5-25 L-2	17	20.5	58.7	25.9	170.9	12PR	25	19180	13560	11990	10190
							29	20750	14640	12960	11020
						174A2	33	22220	15700	13890	11820
							36	23630	16690	14770	12570
						16PR	40	25270	17840	15790	13430
							44	26590	18780	16620	14130
						181A2	47	27870	19690	17420	14820
							51	29100	20550	18190	15450
						20PR	54	30120	21280	18830	16010
							58	31280	22090	19560	16620
						186A2	62	32410	22880	20260	17220
							65	33510	23680	20940	17810

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load			
								Speed			
		Hard Improved Surfaces									
		Static mph	3 mph					6 mph	16 mph		
20.5-25 L-2	17	20.5	58.7	25.9	170.9	12PR	30	21580	17390	16180	14990
							35	23330	18810	17510	16200
						174A2	39	25000	20150	18760	17370
							44	26590	21430	19950	18480
						16PR	48	28420	22880	21320	19730
							52	29920	24100	22440	20790
						181A2	57	31350	25270	23520	21780
							61	32740	26370	24560	22730
						20PR	65	33890	27290	25420	23550
							70	35210	28350	26390	24450
						186A2	74	36460	29390	27360	25330
							78	37700	30380	28290	26190

Note: For above mentioned size 12 PR is no longer active for production.

Grader application