



PRIMEX
FORESTRY

TRA: **HF-4**
Speed Rating: **B**

Primex Logstomper Xtreme Flotation TS features a variable angle lug design that is tapered from the center to the shoulder. This delivers excellent hillside stability, superior traction and exceptional performance in varied ground conditions. The Logstomper Xtreme Flotation TS is engineered with a highly cut and chip resistant compound as well as heavy sidewall and under tread gauges for added protection in demanding service.

AGRICULTURAL LOADER - 66X43.00-26

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load				
								Speed				
								High flotation & Forestry Logging				
		SW inch	OD inch					Static mph	6 mph	9 mph	19 mph	31 mph
66X43.00-26	DW36B	41.5	68.8	30.2	199.4	20PR	29	21470	16950	14180	12020	10740
						174B	36	24470	19340	16160	13710	12240
							44	27210	21500	17950	15230	13600
							50	29540	23350	19490	16540	14770

* Alliance allows for free rolling application: Load capacity to be increased by 20%, after increasing the inflation pressure by 20%. Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

