



PRIMEX  
**AGRICULTURE**

TRA: **HF-3**  
Speed Rating: **B**

Primex Terra Turbo is designed for free-rolling wheels where flotation and limited soil compaction is desired. Terra Turbo provides excellent flotation, solid traction and great wear.

**HIGH FLOTATION/TERRA - 66X43.00-25 NHS**



Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load				
								Speed				
								High floatation application				
		Static mph	6 mph					9 mph	19 mph	31 mph		
66X43.00-25 NHS	36.0TH	40.6	66.5	28.7	200.5	12PR	12	10360	9920	8290	7030	6280
							20	14370	13760	11490	9740	8710
							26	16620	15920	13290	11290	10080
							30	18190	17420	14550	12350	11020
						16PR	12	10580	10140	8470	7190	6420
							23	15900	15210	12720	10780	9630
						170B	32	19180	18360	15340	13010	11620
							40	21830	20900	17460	14820	13230
						20PR	12	10300	9860	8250	6990	6240
							29	17570	16820	14070	11930	10650
							41	21390	20480	17110	14530	12960
							51	24380	23350	19490	16540	14770

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load				
								Speed				
								High floatation application				
		Static mph	6 mph					9 mph	19 mph	31 mph		
66x43.00-25	36.0TH	40.6	68.3	30.0	196.1	26 180B	29	25240	16470	12190	11750	10980
							44	31990	20880	15430	14880	13910
							58	37880	24710	18280	17620	16470
							65	40570	26460	19580	18870	17640