



GALAXY
EARTHMOVER &
MINING

TRA: E-3/L-3
Speed Rating: A2

LDSR 300 is specially constructed for wheel loaders operating in the toughest environments. Transportation of heavy load demands excellent stability and robustness. Sturdy radial construction coupled with strong sidewall protector provides LDSR 300 superior strength and endurance to withstand challenging terrains. Premium tread compounds provide excellent protection against lug-tearing and chunking, helping the machine to perform efficiently without any downtime shaped tread pattern with stepped lugs ensure optimal traction and enhanced self cleaning assuring high productivity.

EARTHMOVER - 29.5R25

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load									
								Speed									
								Load capacity for Loader application kg (lbs)									
		Static mph	Creep mph					3 mph	6 mph	9 mph	12 mph	16 mph	19 mph	25 mph			
29.5R25	25.00/3.5	29.8	73.3	32.3	220.4	216A2	94	79010	64200	56310	49380	42990	41490	39510	38030	34570	

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load											
								Speed											
								Load capacity for Earthmover application kg (lbs)											
		9 mph	12 mph					16 mph	19 mph	22 mph	25 mph	28 mph	31 mph	34 mph	37 mph	40 mph			
29.5R25	25.00/3.5	29.8	73.3	32.3	220.4	200B	76	34610	33950	33290	32630	32190	31750	31530	30870	30200	29100	27120	

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

