



ALLIANCE  
AGRICULTURE  
  
TRA: I-2  
Speed Rating: D

The Agriflex+ 381 is a tire with a flat tread profile and large footprint. It puts more rubber on the ground. This unique rib-type pattern leads to effective steering and improved lateral traction, thereby reducing soil compaction and prolonging tire life. Moreover, the shoulder lugs prevent any excessive tire slips and consequently save the tire surface from further damage.

IMPLEMENT - VF 320/70R15

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load													
		SW inch	OD inch					Speed													
								Static mph	6 mph	16 mph	19 mph	25 mph	31 mph	37 mph	40 mph						
VF 320/70R15	10LBx15	12.6	32.6	14.8	97.7	145D	15	5780	4520	3970	3790	3420	3040	2690	2510						
							22	7300	5710	5030	4780	4320	3840	3400	3180						
							29	8620	6750	5930	5670	5090	4540	4010	3750						
							36	9830	7690	6770	6460	5820	5180	4590	4280						
							44	10960	8580	7520	7190	6480	5750	5090	4760						
							58	12940	10120	8890	8490	7650	6810	6020	5620						
							73	14710	11510	10100	9660	8690	7740	6830	6390						
Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load													
		SW inch	OD inch					Speed													
								Mixed Application													
								Static mph	6 mph	9 mph	12 mph	16 mph	19 mph	22 mph	25 mph	28 mph	31 mph	34 mph	37 mph	40 mph	43 mph
VF320/70R15	10LBX15	10.8	32.8	14.2	97.7	D □ D □ D □ D □	12	4560	3570	3430	3270	3140	3000	2860	2700	2560	2400	2260	2120	1980	1810
							23	7350	5750	5530	5280	5050	4830	4600	4350	4130	3870	3640	3420	3200	2910
							35	8620	6750	6480	6180	5920	5660	5400	5100	4840	4540	4270	4010	3750	3410
							52	10750	8410	8090	7710	7390	7060	6730	6360	6030	5660	5330	5000	4670	4250
							58	13060	10220	9820	9370	8970	8570	8180	7720	7320	6870	6470	6070	5680	5170
							73	14710	11510	11060	10550	10100	9650	9210	8700	8250	7740	7290	6840	6390	5820

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

