

ALLIANCE
AGRICULTURE

TRA: **I-3**
Speed Rating: **B**

Alliance 331 Radial is a traction pattern with good self-cleaning characteristics. It is suitable for on/off road agricultural service on tractors, cross country vehicles, trailers and agricultural implements. High load carrying capacity and low inflation pressure are the main characteristics of this tire. A strong construction with steel belts ensure long life and superior performance for the required application.

IMPLEMENT - 600/45R22.5

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load					
								Speed					
								Mixed application					
		SW inch	OD inch					Static mph	6 mph	16 mph	19 mph	25 mph	31 mph
600/45R22.5	20 AG20.00	23.9	45.4	20.1	137.9	165A8 161B	12	10360	6170	5250	4940	4410	3970
							15	11820	7030	5980	5620	5030	4520
							17	13160	7850	6660	6260	5600	5050
							22	15040	8950	7610	7170	6390	5750
							23	15590	9280	7890	7430	6640	5980
							29	17770	10580	9000	8470	7560	6810
							32	18810	11200	9520	8970	8000	7210
							35	19800	11800	10030	9440	8420	7580
							41	21650	12900	10960	10320	9220	8290
							46	23410	13960	11860	11160	9970	8970
							52	25070	14950	12700	11950	10670	9610
							58	26680	15900	13510	12720	11350	10230

When used in RDT, ADT or construction applications, the applicable warranty will be as per Earth Moving/ Construction application’s warranty policy.