

https://yokohama-atg.com Generated on: 19 Apr, 2024



ALLIANCE **AGRICULTURE**

TRA: **I-3** Speed Rating: **B** Alliance 331 Radial is a traction pattern with good self-cleaning characteristics. It is suitable for on/off road agricultural service on tractors, cross country vehicles, trailers and agricultural implements. High load carrying capacity and low inflation pressure are the main characteristics of this tire. A strong construction with steel belts ensure long life and superior performance for the required application.

IMPLEMENT - 710/50R30.5

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load								
								Speed								
								Mixed application								
		SW inch	OD inch					Static mph	6 mph	16 mph	19 mph	25 mph	31 mph	37 mph	40 mph	43 mph
710/50R30.5	AG24.00	27.6	59.1	26.5	178.7	176D	17	17860	13980	12260	11730	10560	9390	8310	7760	_
							29	24030	18810	16510	15790	14220	12660	11180	10450	_
							41	29260	22910	20110	19200	17310	15390	13600	12720	_
							46	31640	24760	21740	20770	18720	16650	14730	13760	_
							52	33860	26500	23260	22250	20020	17810	15760	14730	_
							58	36000	28180	24740	23630	21300	18940	16760	15650	_

When used in RDT, ADT or construction applications, the applicable warranty will be as per Earth Moving/ Construction application's warranty policy.

