



ALLIANCE
AGRICULTURE

TRA: I-3
Speed Rating: A8

Alliance 380 Implement Flotation tire provides full soil protection and flotation tire characteristics in field. The tires high-speed steel belted radial flotation construction, combined with specific casings construction and special rubber compound enables it to run at high speed on road. Deep non-directional lug type pattern enables high mobility in field including significant traction ability as well as comfortable smooth movement on road. Heavy duty tires are best suited for tough applications compared to the standard range.

IMPLEMENT - 600/55R26.5

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load								
								Speed								
								Mixed Application								
		SW inch	OD inch					Static mph	6 mph	16 mph	19 mph	25 mph	31 mph	37 mph	40 mph	43 mph
600/55R26.5	AG20.00	24.6	53.0	24.3	163.8	168D 165E	12	11160	8730	7670	7320	6590	5860	5180	4850	4430
							22	16120	12610	11070	10580	9520	8490	7500	7010	6390
							29	19070	14930	13100	12520	11270	10030	8860	8290	7560
							36	21690	16980	14900	14240	12830	11420	10100	9440	8620
							51	25110	19640	17240	16470	14840	13210	11680	10910	9970
							58	27140	21230	18630	17810	16050	14260	12610	11800	10760
							73	28400	22220	19510	18650	16800	14950	13210	12350	11350

