

GALAXY  
AGRICULTURE  
  
TRA: **R-1W**  
Speed Rating: **D**

Earth Pro 650 is an extra wide tire available in radial for use in agricultural tractors and combine harvesters for farming. It is characterized by increased load capacity for the same inflation pressure. This means that the low inflation pressure combined with large footprint helps reduce soil compaction. Low angled lugs of the tire at the shoulder area improve traction, while higher angles around the tire center line improve ride comfort. This leads to increased tire traction efficiency by an effective traction/slip characteristic. Also the strong radial construction with reinforced beads and sidewalls provide long tire life.

TRACTOR - 480/65R24

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load									
								Speed									
								1)Not high and sustained torque,2)Road Transport									
								Non cyclic operation									
		Field mph	6 mph					9 mph	12 mph	16 mph	19 mph	25 mph	31 mph	40 mph	43 mph		
480/65R24	W15L W14L	18.9	48.8	21.9	147.6	140D 143A8	17	4230	5530	4940	4520	4370	4230	4030	3860	3680	3350
							23	5000	6530	5820	5340	5140	5000	4760	4560	4340	3950
							29	5710	7450	6660	6110	5890	5710	5420	5200	4960	4520
							35	6350	8270	7390	6790	6530	6350	6040	5800	5510	5030
Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load									
								Speed									
								1)Not high and sustained torque,2)Road Transport									
								Cyclic operation									
		SW inch	OD inch					6 mph		9 mph							
480/65R24	W15L W14L	18.9	48.8	21.9	147.6	140D 143A8	22	6260		5710							
							29	7390		6720							
							36	8440		7690							
							44	9370		8550							

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

