



GALAXY
EARTHMOVER &
MINING

TRA: E-3/L-3
Speed Rating: A2

LDSR 310 is the newest addition to the Galaxy radial OTR tire range. This wheel loader tire is designed with a block tread pattern to make it well-equipped to ply on rocky or hard surfaces with ease. The sturdy all-steel construction coupled with a sidewall protector safeguards the tire against damage. The presence of special compounds provides resistance against wear, lug-tearing, and chunking. Optimal traction, excellent self-cleaning, enhanced riding comfort, and superior durability make LDSR 310 the perfect choice while working in challenging terrains.

EARTHMOVER - 20.5R25

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load									
								Speed									
		Load capacity for Loader application kg (lbs)															
		Static mph	Creep mph					3 mph	6 mph	9 mph	12 mph	16 mph	19 mph	25 mph			
20.5R25	17.00/2.0	20.9	58.8	26.1	171.7	193A2	94	40790	33070	29100	25350	22050	21500	20390	19290	18740	

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load							
								Speed							
		Load capacity for Earthmover application kg (lbs)													
		9 mph	12 mph					19 mph	25 mph	31 mph	37 mph	40 mph			
20.5R25	17.00/2.0	20.9	58.8	26.1	171.7	177B	76	18190	17640	17090	16540	16090	15210	14330	

