






**ALLIANCE
 AGRICULTURE**

TRA:
 Speed Rating: **D**

Alliance 590 is a heavy duty radial flotation tire designed specifically to suit the needs of agriculture and construction applications. A robust steel belted construction with non-directional tread design and superior cut and chip resistant compound enables it to handle heavy Loads and operate both in farms as well as on/off road applications.


SB
STEEL BELTED


CRC
CUT & CHIP RESISTANT COMPOUND


TL
TUBE LESS

IMPLEMENT - 560/60R22.5

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load							
		Speed													
		Mixed Application													
SW inch	OD inch	Static mph	6 mph	12 mph	19 mph	25 mph	31 mph	40 mph	43 mph						
560/60R22.5	AG16.00x22.5	21.7	49.0	22.2	148.6	169D	12	7610	5950	5470	5000	4500	4010	3310	3020
							17	9630	7540	6920	6330	5690	5070	4190	3810
							23	11660	9130	8380	7650	6900	6130	5070	4610
							29	13450	10520	9630	8820	7940	7080	5840	5310
							35	15590	12210	11180	10230	9220	8200	6780	6170
							41	17510	13690	12540	11490	10340	9190	7610	6920
							46	19640	15390	14090	12900	11620	10340	8540	7780
							52	21560	16870	15450	14150	12740	11330	9370	8530
							58	23460	18360	16820	15390	13870	12350	10200	9280
							73	26130	20440	18740	17150	15430	13740	11350	10340
							87	29410	23020	21100	19310	17390	15480	12790	11640

