



ALLIANCE
AGRICULTURE

TRA: **R-1W**
Speed Rating: **D**

The Alliance 365 (High-Speed Drive Tractor Radial) tires are available in a complete range of front and rear combination tires. The tread patterns on these tires represent the trend of modern radial agricultural tires with a low aspect ratio. High tire volume along with low inflation pressure provides high traction and increased soil protection. The lug design ensures better self-cleaning with reduced tire slippage. Multi lug angle tread pattern and over-lapping central lugs ensure on & off-road suitability

TRACTOR - 480/65R28

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load						
								Speed						
								Non Cyclic Operation						
		NaN mph	Field mph					6 mph	16 mph	25 mph	31 mph	40 mph		
480/65R28	W15L X 28 W14L X 28	19.1	52.6	24.6	161.2	142D 145A8	12	3680	3680	4810	3790	3510	3350	3200
							23	5690	5690	7410	5840	5400	5180	4940
							35	6720	6720	8770	6920	6390	6130	5840
Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load						
								Speed						
								Cyclic Operation						
		SW inch	OD inch					6 mph	9 mph					
480/65R28	W15L X 28 W14L X 28	19.1	52.6	24.6	161.2	142D 145A8	15	5450	4960					
							29	8400	7650					
							44	9940	9060					

* Alliance allows for free rolling application: Load capacity to be increased by 20%, after increasing the inflation pressure by 20%.

