



ALLIANCE  
AGRICULTURE  
  
TRA: **R-1**  
Speed Rating: **A8**

Alliance 768 Value Plus is specially designed to meet the unique demands of pivot irrigation. Built with strong nylon carcass construction which enhances its ability to carry continuous heavy loads. Designed with low lug angles and rounded shoulders for optimal traction and maximum crop protection. The presence of special ozone compound protects it from cracking ensuring excellent durability.

TRACTOR - 11.2-38

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load										
								Speed										
								Tractor Application										
		SW inch	OD inch					Static mph	3 mph	6 mph	9 mph	12 mph	16 mph	19 mph	22 mph	25 mph	28 mph	31 mph
11.2-38	W10X38	11.2	57.3	26.8	171.0	6 114A8	12	3700	2730	2430	2160	1980	1790	1720	1650	1610	1540	1460
							17	5070	3480	3090	2760	2510	2270	2210	2120	2050	1960	1870
							20	5530	3810	3370	3020	2760	2490	2400	2320	2250	2160	2050
							23	5580	4120	3640	3240	2980	2690	2600	2490	2430	2340	2210
							26	6390	4430	3900	3480	3200	2890	2780	2690	2600	2490	2360

