




**ALLIANCE
 AGRICULTURE**

TRA: **R-1W**
 Speed Rating: **B**



The advanced Agriflex 372 Improved Flexion (IF) designed with increased sidewall flexibility enables the tire to carry (up to 20%) more load at the same pressure as compared to a standard tractor radial. It offers a significantly large footprint leading to low soil compaction and a comfortable ride for the driver. The larger footprint enables high traction, reduces fuel costs and increases overall operation productivity. The R-1W pattern enables excellent grip as well as long tire life on hard surfaces.

TRACTOR RADIAL HIGH SPEED - IF 420/85R28

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load				
								Speed				
		Not high and sustained torque; Road transport										
		6 mph	9 mph					12 mph	40 mph	43 mph		
IF 420/85R28	W15, W14	17.6	56.6	25.0	167.8	145D	12	5090	4560	4190	4080	3700
							15	5840	5230	4780	4670	4260
							17	6500	5820	5340	5200	4740
							20	7300	6530	6000	5840	5310
							23	8000	7140	6550	6390	5820

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load
								Speed
		Cyclic*						
		6 mph						
IF 420/85R28	W15, W14	17.6	56.6	25.0	167.8	145D	15	6320
							19	7240
							22	8060
							26	9060
							29	9910

Highlighted column indicates speed limit 25kmph to 65kmph



Interpolation for intermediate data (speed and pressure) is possible

Cyclic values are for service with a front loader and should not exceed a distance of 1.0 km

For CFO operation max. distance should not exceed 1.5 km

For dual configuration with tabulated pressures: 88% of load as single is approved

For triple configuration with tabulated pressures: 82% of load as single is approved

For dual and triple configuration it is possible to inflate min. of 0.4 bar, consult your dealer