



**ALLIANCE
CONSTRUCTION &
INDUSTRIAL**

TRA: **R-4**
Speed Rating: **A2**

The Alliance SK-903 is a specialized tire developed for Skid Steer application. The open and deep shoulders are designed for traction on loose off-road surfaces. The flatter radius of the tire improves the wear resistance. Solid center lug for improved wear resistance. Rim Shield Protector on sidewall for shock protection



OTHERS



TEXTILE(T)

SKIDSTEER - 12X16.5NHS

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load		
		SW inch	OD inch					Speed		
								Backhoe	Skid Steer	
								25 mph	Static mph	6 mph
12X16.5NHS	9.75	12.1	32.7	15.0	98.8	10 140A2	65	3700	8850	5600

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load		
		SW inch	OD inch					Speed		
								Backhoe	Skid Steer	
								25 mph	Static mph	6 mph
12X16.5NHS	9.75	12.1	32.7	15.0	100.5	12 144A2	80	3980	9980	6320

