



ALLIANCE  
AGRICULTURE  
  
TRA: **R-4**  
Speed Rating: **A8**

550 MULTIUSE pattern is used in agricultural applications because of its versatile tread design. Specific block tread design enables high performances on snow-covered as well as on sandy terrains. A basic directional lug design, divided by separated blocks, provides a good grip on soft surfaces. In addition, a high number of blocks and rubber-to-void tread ratio enables long tread wear life and low rolling resistances during transport operation on hard surfaces. Uniform ground pressure distribution and tread wear are provided by steel belted carcass structure. In addition, steel belts give the most efficient puncture protection.

TRACTOR - 400/80R24IND(14.9R24IND)

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load									
								Speed									
		Constant load								Cyclic operation							
		Static mph	6 mph					12 mph	19 mph	25 mph	31 mph	40 mph	43 mph	6 mph	9 mph		
400/80R24IND(14.9R24IND)	W13X24	15.9	49.2	22.3	146.9	149A8 144D	12	7480	4080	3570	3400	3260	3060	2830	2580	4890	4370
							23	11640	6350	5560	5290	5070	4760	4410	4010	7630	6790
							35	13740	7490	6560	6240	5980	5620	5200	4740	9000	8000
							46	16300	8890	7780	7410	7100	6670	6170	5620	10670	9500

