

ALLIANCE
AGRICULTURE

TRA: **I-3**
Speed Rating: **A8**

Alliance 380 Implement Flotation tire provides full soil protection and flotation tire characteristics in field. The tires high-speed steel belted radial flotation construction, combined with specific casings construction and special rubber compound enables it to run at high speed on road. Deep non-directional lug type pattern enables high mobility in field including significant traction ability as well as comfortable smooth movement on road. Heavy duty tires are best suited for tough applications compared to the standard range.

IMPLEMENT - 710/45R22.5

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load								
								Speed								
								Mixed application								
		SW inch	OD inch					Static mph	6 mph	16 mph	19 mph	25 mph	31 mph	37 mph	40 mph	43 mph
710/45R22.5	AG24.00	28.6	47.6	21.0	145.0	165D	12	9280	7630	6920	6460	5840	5250	4670	4390	4030
							22	13450	11050	10080	9350	8470	7610	6770	6370	5840
							29	15870	13050	11880	11050	10010	8970	8000	7520	6900
							36	18100	14880	13560	12590	11420	10230	9130	8580	7870
							44	20130	16540	15080	14000	12700	11380	10160	9550	8750
							51	22000	18080	16470	15300	13870	12430	11090	10430	9570
							58	26130	20440	17950	17150	15430	13740	12150	11350	10340

1) When fitted on tractor steering wheels load capacitiy is 80% of free rolling and inflation pressure 20% higher. " 2) For 10 km/h and stationary use inflation pressure raised 20% and 25% respectively