



ALLIANCE
AGRICULTURE

TRA: I-2
Speed Rating: D

Alliance 381 Agriflex is an IF steel belted radial flotation tire that has been developed to serve the needs of specific niche applications on sensitive surfaces, which require optimized soil and plant protection. The unique rib type pattern, enables a large footprint and low ground pressure. The shoulder lugs prevent any excessive tire slip and any consequent damage to the surface. Its specially designed bead area ensures better load carrying capacity.

IMPLEMENT - IF 280/70R15

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load							
								Speed							
								Mixed application							
		SW inch	OD inch					Static mph	6 mph	16 mph	19 mph	25 mph	31 mph	37 mph	40 mph
IF 280/70R15	W8	11.0	30.5	13.8	90.7	137D	35	7720	6040	5290	5070	4560	4060	3590	3350
							38	8070	6310	5530	5290	4760	4230	3750	3510
							41	8420	6590	5780	5530	4980	4430	3920	3660
							44	8770	6860	6020	5750	5180	4610	4080	3810
							46	9130	7140	6260	6000	5400	4810	4260	3970
							49	9480	7430	6500	6220	5600	4980	4410	4120
							52	9830	7690	6770	6460	5820	5180	4590	4280
							55	10140	7940	6970	6660	6000	5340	4720	4410
							58	10490	8220	7210	6900	6220	5510	4870	4560
							61	10760	8420	7390	7060	6350	5670	5000	4670
							64	11050	8640	7580	7250	6530	5820	5140	4810
							67	11350	8890	7800	7450	6720	5980	5290	4940
							70	11660	9130	8000	7650	6900	6130	5420	5070

Note :- The production of the above mentioned size has been discontinued . Please click below to view the details of the replaced size <http://www.atgtire.com/ShowAllianceDesignDetails.aspx?id=1633>

