



ALLIANCE
AGRICULTURE

TRA: I-2
Speed Rating: D

Alliance 390 Heavy Duty steel belted flotation radial Implement tires belong to the Agri-Transport series combining the best of flotation characteristics with the best of radial construction characteristics to provide excellent performance both on and off road. The tires can be used for multiple machines in on/off-the-road applications. MPT tires can drive upto 100 km/h and are best suited for tough applications compared to the standard range.

HEAVY DUTY FLOTATION - 710/65R26

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load							
								Speed							
								Mixed Application							
		SW inch	OD inch					Static mph	6 mph	16 mph	19 mph	25 mph	31 mph	37 mph	40 mph
710/65R26	DW 25	28.7	61.8	27.7	186.7	187D	12	16030	12540	11000	10520	9480	8420	7450	6970
							17	20330	15920	13980	13360	12020	10690	9460	8840
							22	23130	18100	15870	15190	13670	12170	10760	10050
							23	24030	18810	16510	15790	14220	12660	11180	10450
							29	27380	21430	18810	17970	16180	14400	12740	11910
							35	30470	23850	20940	20020	18010	16030	14180	13250
							41	33360	26100	22930	21910	19730	17550	15520	14510
							46	36110	28260	24800	23700	21340	19000	16800	15700
							52	38690	30270	26590	25400	22880	20350	17990	16820
							58	41180	32230	28290	27030	24340	21670	19160	17900
							64	43500	34040	29900	28570	25730	22880	20240	18920
							73	46910	36710	32230	30800	27730	24670	21830	20390
							87	49450	38690	33970	32450	29230	26020	22990	21500

